

GENUINE G560



















FEATURES

- · Futuristic duotone aluminum heatsink
- · Supports the latest Microsoft DirectStorage
- DRAM cache buffer to extend SSD lifespan, enhance runtime performance, and strengthen the durability all at once
- · Supports AES 256-bit Hardware-based Encryption to ensure superior data security Intelligent SLC caching algorithm for high endurance and performance improvement
- Powerful Hardware LDPC ECC Engine for endurance and retention improvement
- Supports Global Wear Leveling for SSD lifespan extension
- · Thermal throttling algorithm to protect the SSD integrity
- Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)

SPECIFICATIONS

Host Interface	NVMe PCIe Gen5x4	
Form Factor	M.2 2280	
Capacity	1TB, 2TB, 4TB	
Controller	Phison E26	
Flash	strictly-selected 3D TLC NAND Flash	
Dimension(LxWxH)	80.5 x 23.35 x 17.8 mm (with heatsink)	
Weight	68g	
Warranty	5-year limited warranty	

PERFORMANCE

	1TB	2TB	4TB
Sequential Read up to (MB/s)	13000	14000	14000
Sequential Write up to (MB/s)	9500	12000	12000
4K Random Read up to (IOPS)	1300K	1400K	1400K
4K Random Write up to (IOPS)	1400K	1400K	1400K
Endurance (TBW)	700	1400	3000

ORDERING INFORMATION

Capacity	Product Number	EAN Code
1TB	K01TBM2SP0-G56	4895194901761
2TB	K02TBM2SP0-G56	4895194901778
4TB	K04TBM2SP0-G56	4895194901785







